

FIBREroll EW 30 / 45 / 60

TEXTILE ROLLER FIRE CURTAIN

FIRE RESISTANCE:

E 30 / EW 30, E 60 / EW 45, E 120 / EW 60



PRODUCT DESCRIPTION

- » Made of special fire-resistant textile 0.7 thick, reinforced by stainless steel wires with surface coating and aluminium reflecting coating (foil) to increase fire resistance
- » **Maximum total width 16 m, maximum total height 7 m, for EW 60-C0 maximum total width 4,8 m, maximum total height 4,5 m**
- » Up to total dimension 3 × 3 m smoke-tight version is available with fire resistance **EW 60-C0S_a** or **EW 60-C0S₂₀₀**
- » Minimum total width 1000 mm
- » Designed for face fixing or fixing between assembly (possible combination of both), fixing into concrete, masonry or steel profiles with required fire resistance
- » Standard **dimension of the box is 200 × 200 mm (W × H)** with total height up to 6 × 3,2 m (W × H), for bigger dimensions or smoke-tight version of curtain the size of the box is **230 × 230 mm (W × H)**
- » Very light (curtain 3 × 3 m approx. 140 kg, curtain 6 × 6 m approx. 300 kg)
- » Controlled electrically by means of a tube drive (230 V)
- » **Control panel AOP** (Avaps Operation Panel) **including emergency closure button**
 - » System designed in accordance with **EN 14637**
- » Ensures electronic control of individual curtain functions
- » **“Fail safe”** – safe gravity closure even in the event of a power failure, status monitoring and fault evaluation (short circuit, cabling failure, undervoltage, preload,...)
- » Fire detection options: local Fire Alarm System (potential-free contact) or local detection (3 or 6 sensors depending on the closure width)
- » Contains its own back-up power source (accumulator) to prevent unwanted closing of the curtain in case of power failure, including a cyclic charging system that extends battery life
- » According to customer requirements can be supplemented with:
 - key switch, lockable button
 - optical and acoustic signalling
 - signalling of conditions to external devices
- » Closing speed is approximately 100 mm/s
- » Steel parts are made from galvanized metal, standardly powder coated in **RAL 9006** (white aluminium) or **RAL 9010** (white), alternatively, atypical coating according to the RAL sampler possible at the customer's request



CERTIFICATION


Fire curtain **FIBREroll** has been successfully tested in fire testing centre FIRES s.r.o., classified as per EN 15269-11 and EN13501-2, assessed as per EN 13241+A2 and EN 16034 and is covered by CE certificate No. 1396-CPR-0154. / For more information, contact projekce@avaps.cz.

Manufacturer issues declaration of performance for individual orders in compliance with Regulation of the European Parliament and Council (EU) No. 305/2011.




TECHNICAL INFORMATION


VIEW - FIXING INTO THE OPENING (FIXED BETWEEN)




TYPICAL SECTION FIXED BETWEEN




TYPICAL SECTION FACE FIXED




PLAN VIEW - FIXING INTO THE OPENING (FIXED BETWEEN)



PLAN VIEW - FIXING ONTO THE OPENING (FACE FIXED)



SIDE GUIDE FIXING DETAIL
FACE BETWEEN FACE FIXED



This drawing and copyright belong to Avaps s.r.o. Do not copy without Avaps s.r.o. authorisation.

MAINTENANCE AND REPAIR SERVICES

We provide professional warranty and post-warranty service and revisions according to applicable laws for all our products.

Contact: +420 777 911 780 / service@avaps.eu

